

**Steckfitting PN 16 Best.-Nr. 616**

Rohr - Außen - ø	32	40	32	40	50	63
ZAK® - Anschluss	ZAK 34	ZAK 34	ZAK 46	ZAK 46	ZAK 46	ZAK 46
Gewicht kg	0,50	0,70	0,70	0,80	1,20	1,60



**Winkel - Steckfitting 90° PN 16 Best.-Nr. 6475**

Rohr - Außen - ø	32	40	32	40	50	63
ZAK® - Anschluss	ZAK 34	ZAK 34	ZAK 46	ZAK 46	ZAK 46	ZAK 46
Gewicht kg	0,80	1,10	0,90	1,20	1,65	2,10



**Winkel - Drehsteckfitting 90° Best.-Nr. 6465  
PN 16**

Rohr - Außen - ø	32	40	32	40	50	63
ZAK® - Anschluss	ZAK 34	ZAK 34	ZAK 46	ZAK 46	ZAK 46	ZAK 46
Gewicht kg	1,60	1,80	1,70	1,90	2,30	2,80



**Winkel - Drehsteckfitting 90° Best.-Nr. 6466 N  
PN 16**

Rohr - Außen - ø	40	40	50	
ZAK® - Anschluss	ZAK 34	ZAK 46	ZAK 46	
Gewicht kg	2,35	2,35	2,70	

Konusring demontierbar



**PE - Ende PN 4 / PN 10 Best.-Nr. 618**

Rohr - Außen - ø	32	40	32	40	50	63
ZAK® - Anschluss	ZAK 34	ZAK 34	ZAK 46	ZAK 46	ZAK 46	ZAK 46
Gewicht kg	0,50	0,96	0,60	0,60	0,90	1,20



**Winkel - PE - Ende PN 4 / PN 10 Best.-Nr. 6479**

Rohr - Außen - ø	32	40	32	40	50	63
ZAK® - Anschluss	ZAK 34	ZAK 34	ZAK 46	ZAK 46	ZAK 46	ZAK 46
Gewicht kg	0,80	0,90	1,00	0,65	0,85	1,30

