

## Bügel ( Haltestück ) für das Universal - Schellensystem Fabrikat HAWLE

Bügel – nichtrostender, säurebeständiger St. Best.-Nr. 311



Best.-Nr.	Rohr - Außen-ø mm	für Hauptrohr - DN					Bau- Länge mm	Gewicht kg
		St.	St.-PE	Guss	Guss-PE	Guss-ZM		
311.080.0365	75 - 88	65	65			65	365	0,75
311.080.0375	79 - 92						375	0,75
311.080.0400	90 - 103		80	80	80		400	0,75
311.100.0435	104 - 114					80	435	0,80
311.100.0445	107 - 120						445	0,80
311.100.0450	110 - 123	100	100	100	100		450	0,80
311.100.0460	116 - 128				100	100	460	0,80
311.100.0490	126 - 139						490	0,90
311.125.0520	138 - 151	125	125	125	125		520	0,90
311.125.0540	146 - 158				125	125	540	0,90
311.150.0570	157 - 169	150					570	0,95
311.150.0595	166 - 178	150	150	150	150		595	0,95
311.150.0620	175 - 188						620	0,98
311.150.0630	178 - 191					150	630	1,00
311.175.0645	183 - 196						645	1,00
311.200.0685	199 - 210						685	1,05
311.200.0710	208 - 220	200					710	1,05
311.200.0725	213 - 225						725	1,10
311.200.0745	220 - 232	200	200	200	200	200	750	1,10
311.200.0770	229 - 241						770	1,10
311.225.0800	239 - 251						800	1,15
311.225.0830	250 - 262						830	1,15
311.250.0865	262 - 274	250		250			865	1,20
311.250.0905	275 - 287					250	905	1,20
311.275.0935	286 - 298						935	1,25
311.300.0975	299 - 311						975	1,30
311.300.0995	306 - 318						995	1,30
311.300.1035	319 - 331	300	300	300	300		1035	1,35
311.300.1055	326 - 337		300		300		1055	1,40
311.300.1085	334 - 346						1085	1,40
311.300.1120	347 - 358	350					1120	1,45
311.350.1155	359 - 370		350				1155	1,45
311.350.1205	375 - 387				350		1205	1,50
311.350.1270	396 - 409	400					1270	1,55
311.400.1345	419 - 434			400	400		1345	1,65
311.400.1392	435 - 449					400	1392	1,70